



ENERG

енергия · ενεργεια



GENVEX A/S

GE ENERGY 2 V3



41
dB



445 m³/h



ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2016

1254/2014

Technical Product Fiche

Suppliers name	GENVEX A/S
Model identification	GE Energy 2 V3
Specific energy consumption SEC kWh/(m ² *a) for: cold, average, warm climates	SECcold: -73,4 ; SECAverage : -37,4 ; SECwarm: -14,1
RVU/NRVU/Unidirectional / Bidirectional	RVU - Bidirectional
Type of drive installed	EC motor with 0-100 % modulation range
Type of heat recovery (recuperative, regenerative, non)	Recuperative
Thermal efficiency of heat recovery %	79
Maximum airflow (m ³ /h)	445
Electric Power input of fan drive at maximum airflow - W	162
Sound Power level (Lwa) at reference airflow Lwa	41
Reference airflow rate (m ³ /s)	0,086
Reference pressure difference (min. 50Pa) – (Pa)	50
Specific power input at reference airflow – SPI / SEL (W/ m ³ /h)	0,24
Control factor	0,85
Declared maximum internal and external leakage rates (%)	Internal: 0,9 % ; External: 1,4 %
Mixing rate of non ducted bidirectional ventilation units	Not applicable
Position and description of visual filter warning	After a specific time the display will tell that it is time to clean the filters or replace them with new ones.
Instructions for installing supply/exhaust grilles i facade for unidirectional devices	Not applicable
Internet adress for pre-/disassembly instructions	www.genvex.dk (manual)
Sensitivity for pressure variation for units without ducts + and - 20Pa	Not applicable
For non ducted units - the indoor/outdoor air tightness in (m ³ /h)	Not applicable
The annual electricity consumption AEC per 100 m ² (kWh electricity /a) for climates : Average, Warm, Cold	AECcold=801 ; AECAverage=264 ; AECwarm=219
The annual heating saved AHS in primary energy (kWh prim/a) per 100 m ² for climates : Average, Warm, Cold	AHScold=8469 ; AHSaverage=4329 AHSwarm=1958