

# A+ RH SENSOR MODULE



- Easy and fast installation, no wiring, RF technology
- Capacitive button for manual control
- Battery powered

## Application

The sensor module is a device to measure air quality in a residential environment. The typical application is to measure indoor humidity in wet rooms and send this via RF to a Genvex ventilation unit.

The ventilation unit can react on the information from the sensor accordingly.

With the capacitive button a manual control function can be selected.



## Technical details

### Material

Casing front and back: ABS plastics

### Size

100 x 100 x 30 mm (b x h x d)

### Power supply

Battery: 2x AA minimal 3 years

### Communication

Honeywell 868 MHz RF protocol.

Multipoint bi directional communication

### Environmental conditions

Temperature: - in operation: 4...40°C.

- transportation: -20...55°C.

Relative humidity battery powered: 5..100% condensing

### User Interface

Capacitive button: 1

4 LED's : Green

bicolor LED: Red/Green

### Mounting

On wall (over a flush mounted box)

### Certifications

ETSI EN 300 220-1:

- Electromagnetic compatibility and Radio spectrum Matters (ERM);
- Short Range Devices (SRD);
- Radio equipment to be used in the 25 MHz to 1000 MHz frequency range with power levels ranging up to 500 mW;
- Part 1: Technical characteristics and test methods
- For a class 1F application

EN61000-6-3:2007 emission standard, residential, commercial and light industry.

EN61000-6-1:2007 immunity standard, residential, commercial and light industry.

NEN-EN 60730-1:2007

"Automatic electrical controls for household and similar use

Part 1: general requirements".

RohS and WEEE compliant

## Sensor specifications

### Humidity

Response time 5 s 1/e in slow moving air

Long-term stability 1.2 %RH for five years;

0.25 %RH each year

Operating hum. Range 0 %RH to 100 %RH

Accuracy  $\pm 3.5$  %RH  $\pm 3$  %RH

## Typical application

As a battery powered humidity sensor in the kitchen or bathroom

- It measures the relative humidity and sends out a signal via RF to the Genvex ventilation unit to speed up (or slow down) to a default defined ventilation speed.
- Capacitive button will be used to bind RF and is used for manual control.
- LED's