




# ENERG

енергия · ενεργεια



GENVEX A/S

GE ENERGY 1



44  
dB



312 m<sup>3</sup>/h



ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2016

1254/2014

### Technical Product Fiche

Suppliers name	GENVEX A/S
Model identification	GE Energy 1
Specific energy consumption SEC kWh/(m <sup>2</sup> *a) for: cold, average, warm climates	SECcold: -72,7 ; SECAverage : -36,8 ; SECwarm: -13,6
RVU/NRVU/Unidirectional / Bidirectional	RVU - Bidirectional
Type of drive installed	EC motor with 0-100 % modulation range
Type of heat recovery (recuperative, regenerative, non)	Recuperative
Thermal efficiency of heat recovery %	78
Maximum airflow (m <sup>3</sup> /h)	312
Electric Power input of fan drive at maximum airflow - W	126
Sound Power level (Lwa) at reference airflow Lwa	44
Reference airflow rate (m <sup>3</sup> /s)	0,061
Reference pressure difference (min. 50Pa) – (Pa)	50
Specific power input at reference airflow – SEL/ SPI (W/ m <sup>3</sup> /h)	0,263
Control factor	0,85
Declared maximum internal and external leakage rates (%)	Internal: 0,9% ; External: 1,1%
Mixing rate of non ducted bidirectional ventilation units	Not applicable
Position and description of visual filter warning	After a specific time the display will tell that it is time to clean the filters or replace them with new ones.
Instructions for installing supply/exhaust grilles i facade for unidirectional devices	Not applicable
Internet adress for pre-/disassembly instructions	www.genvex.dk (manual)
Sensitivity for pressure variation for units without ducts + and - 20Pa	Not applicable
For non ducted units - the indoor/outdoor air tightness in (m <sup>3</sup> /h)	Not applicable
The annual electricity consumption AEC per 100 m <sup>2</sup> (kWh electricity /a) for climates : Average, Warm, Cold	AECcold=820 ; AECAverage=280 ; AECwarm=238
The annual heating saved AHS in primary energy (kWh prim/a) per 100 m <sup>2</sup> for climates : Average, Warm, Cold	AHScold=8442 ; AHSaverage=4316 AHSwarm=1952